Agency Read Campaign By Id

API URI

```
https://api.versal.one/<uuid>
```

```
GET /agency/getCampaign/<campaign id>
```

Description

This API allows fetching campaign details by providing the campaign `id` and the `uuid` of the company. The endpoint returns campaign data if found, otherwise, a message indicating no data found.

Request Headers

Header	Type	Description	Constraints
`Authorization`	String	JWT token for user authentication and authorization.	Required. Must be in the format `Bearer [token]`.

Request Parameters

Field	Type	Description	Constraints
`id`	String	ID of the campaign to fetch.	Required.
`uuid`	String	UUID of the company or user associated with the campaign.	Required.

Response Codes

Status Code	Description
`200`	Success. Campaign data retrieved successfully.

Status Code	Description
`204`	No Content. No campaign found for the provided ID.
`400`	Bad Request. Campaign ID is required.
`401`	Unauthorized. Invalid or missing JWT token.
`404`	Not Found. No company found with the provided UUID or no campaign found with the ID.
`500`	Internal Server Error. An unexpected error occurred while fetching the campaign data.
`403`	Forbidden. Invalid HMAC signature.

Example Requests

Request (Get Campaign):

```
GET 53d1bcd3-aaf0-45e1-9298-5395b6a27b61/agency/getCampaign/12345
Authorization: Bearer 5395b6a27b61
```

Response (Campaign Found - 200):

```
{
  "success": true,
  "message": "Successfully fetched campaign data.",
  "data": [
    {
      "id": "12345",
      "uuid": "53d1bcd3-aaf0-45e1-9298-5395b6a27b61",
      "name": "Campaign Name",
      "status": "active",
      "startDate": "2025-01-01",
      "endDate": "2025-12-31"
    }
  ]
}
```

Response (No Campaign Found - 204):

```
{
  "success": true,
  "message": "No campaign data found.",
  "data": []
}
```


Response (Missing Campaign ID - 400):


```
{
  "success": false,
  "message": "Campaign ID is required."
}
```


Response (No Company Found - 404):


```
{
  "success": false,
  "message": "No company found with the provided uuid"
}
```


Response (Internal Server Error - 500):


```
{
  "success": false,
  "message": "An unexpected error occurred while fetching the campaign by id. Please try again later."
}
```


Response (Invalid HMAC Signature - 403):


```
{
  "success": false,
  "message": "Forbidden: Invalid HMAC signature"
```

```
}
```

Notes

- **Authentication**: Ensure the JWT token is valid and authorized to access campaign data.
- **Validation**: Both `id` and `uuid` are required. Missing any of these will result in a 400 or 404 error.
- **Error Handling**: For any server errors (500), check the logs for detailed error information.

Revision #3
Created 2025-01-16 00:35:44 UTC
Updated 2025-10-03 06:04:15 UTC by Admin