

Agency Read Campaign By Id

API URI

https://api.versal.one/<uuid>

GET /agency/getCampaign/<campaign id>

Description

This API allows fetching campaign details by providing the campaign `id` and the `uuid` of the company. The endpoint returns campaign data if found, otherwise, a message indicating no data found.

Request Headers

Header	Type	Description	Constraints
Authorization	String	JWT token for user authentication and authorization.	Required. Must be in the format <code>Bearer [token]</code> .

Request Parameters

Field	Type	Description	Constraints
id	String	ID of the campaign to fetch.	Required.
uuid	String	UUID of the company or user associated with the campaign.	Required.

Response Codes

Status Code	Description
200	Success. Campaign data retrieved successfully.

Status Code	Description
204	No Content. No campaign found for the provided ID.
400	Bad Request. Campaign ID is required.
401	Unauthorized. Invalid or missing JWT token.
404	Not Found. No company found with the provided UUID or no campaign found with the ID.
500	Internal Server Error. An unexpected error occurred while fetching the campaign data.
403	Forbidden. Invalid HMAC signature.

Example Requests

Request (Get Campaign):

```
GET 53d1bcd3-aaf0-45e1-9298-5395b6a27b61/agency/getCampaign/12345
Authorization: Bearer 5395b6a27b61
```

Response (Campaign Found - 200):

```
{
  "success": true,
  "message": "Successfully fetched campaign data.",
  "data": [
    {
      "id": "12345",
      "uuid": "53d1bcd3-aaf0-45e1-9298-5395b6a27b61",
      "name": "Campaign Name",
      "status": "active",
      "startDate": "2025-01-01",
      "endDate": "2025-12-31"
    }
  ]
}
```

Response (No Campaign Found - 204):

```
{
  "success": true,
  "message": "No campaign data found.",
  "data": []
}
```

Response (Missing Campaign ID - 400):

```
{
  "success": false,
  "message": "Campaign ID is required."
}
```

Response (No Company Found - 404):

```
{
  "success": false,
  "message": "No company found with the provided uuid"
}
```

Response (Internal Server Error - 500):

```
{
  "success": false,
  "message": "An unexpected error occurred while fetching the campaign by id. Please try again later."
}
```

Response (Invalid HMAC Signature - 403):

```
{
  "success": false,
  "message": "Forbidden: Invalid HMAC signature"
}
```

Notes

- **Authentication:** Ensure the JWT token is valid and authorized to access campaign data.
 - **Validation:** Both `id` and `uuid` are required. Missing any of these will result in a 400 or 404 error.
 - **Error Handling:** For any server errors (500), check the logs for detailed error information.
-

Revision #3

Created 16 January 2025 06:05:44 by Lokesh Ravi

Updated 17 January 2025 04:29:33 by Admin