

# Agency Sync

## API URI

https://api.versal.one/<uuid>

## Method

POST /agency/sync

## Description

This API synchronizes agency data using a unique identifier (`uuid`). The client must provide an authorization token to access this endpoint. The API responds with success, error, or status messages based on the input and server-side processes.

## Request Headers

Header	Type	Description	Constraints
<code>Authorization</code>	String	Bearer token for authentication and authorization.	Required. Must be in the format <code>Bearer [token]</code> .

## Query Parameters

Parameter	Type	Description	Constraints
<code>uuid</code>	String	Unique identifier for the agency.	Required. Must be a valid UUID format.

## Response Codes

Status Code	Description
<code>200</code>	Sync completed successfully. Returns a success message.
<code>400</code>	Bad request. The <code>uuid</code> parameter is missing or invalid.
<code>403</code>	Access forbidden. Invalid HMAC signature.
<code>404</code>	No agency found with the provided <code>uuid</code> .

Status Code	Description
500	Internal server error. Something went wrong on the backend.

## Example Requests

### Request (Sync Agency):

```
POST /53d1bcd3-aaf0-45e1-9298-5395b6a27b61/agency/sync
Authorization: Bearer 5395b6a27b61
```

### Response (Sync Complete - 200):

```
{ "status": true, "message": "Sync Complete" }
```

### Response (Missing UUID - 400):

```
{ "success": false, "message": "Bad Request: Missing uuid parameter" }
```

### Response (Invalid HMAC - 403):

```
{ "success": false, "message": "Forbidden: Invalid HMAC signature" }
```

### Response (Not Found - 404):

```
{ "success": false, "message": "No company found with the provided uuid" }
```

### Response (Server Error - 500):

```
{ "status": false, "message": "Something went wrong on the backend" }
```

## Notes

- **Authentication:** The authorization token must be valid. If it is missing or invalid, the request will fail.
- **Field Validation:** Ensure the `uuid` parameter is correctly formatted as a valid UUID.
- **Error Handling:** For 500 errors, consult server logs for debugging.

Revision #3

Created 16 January 2025 05:25:06 by Lokesh Ravi

Updated 17 January 2025 04:06:41 by Admin