Agency Template Reporting

API URI

```
https://api.versal.one/<uuid>
```

```
POST /agency/template
```

Description

This API enables agencies to submit and track template information. The client must provide a valid `uuid` as a query parameter and include the template details in the request body. If the `wam_id` is not provided, the template will automatically be reported as failed.

Request Headers

Header	Type	Description	Constraints
`Authorization`	String	Bearer token for authentication and authorization.	Required. Must be in the format `Bearer [token]`.

Query Parameters

Parameter	Type	Description	Constraints
`uuid`	String	Unique identifier for the agency.	Required. Must be a valid UUID format.

Request Body Parameters

Field	Type	Description	Constraints
`template_name`	String	Name of the template to be tracked.	Required.
`phone_number`	String	Phone number associated with the template.	Required.
`wam_id`	String	Unique identifier for the WhatsApp template. If not provided, the template will be reported as failed.	Optional.

Response Codes

Status Code	Description
`403`	Forbidden. Invalid HMAC signature.
`400`	Bad request. Missing `uuid` parameter or required fields in the request body.
`404`	No company found with the provided `uuid`.
`500`	Failed to save data to MongoDB or process the template data.

Example Requests

Request (Track Template):

```
POST 53d1bcd3-aaf0-45e1-9298-5395b6a27b61/agency/template
Authorization: Bearer 5395b6a27b61
{
 "template_name": "savetem",
 "phone_number": "6363978748",
 "wam_id": "wamkskdfj-lkskfdkskf"
}
```

Response (Success - 200):

```
{ "success": true, "message": "Template data processed successfully" }
```

Response (Missing UUID - 400):

```
{ "success": false, "message": "Bad Request: Missing uuid parameter" }
```

Response (Missing Fields - 400):

```
{ "success": false, "message": "Template name and phone number are required" }
```

Response (Invalid HMAC - 403):

```
{ "success": false, "message": "Forbidden: Invalid HMAC signature" }
```

Response (No Company Found - 404):

```
{ "success": false, "message": "No company found with the provided uuid" }
```

Response (MongoDB Failure - 500):

```
{ "success": false, "message": "Failed to save data in MongoDB. Please try again later." }
```

Response (Unexpected Error - 500):

```
{ "success": false, "message": "An unexpected error occurred while processing the template data. Please try again later." }
```

Notes

- **Authentication**: The authorization token must be valid and properly formatted. Invalid or missing tokens will result in a 403 error.
- **Field Validation**: The `template_name` and `phone_number` fields are required for this request.
- **WAM ID Handling**: If `wam_id` is not provided, the template will automatically be reported as failed.
- **Error Handling**: For 500 errors, consult server logs for more details.

Revision #3
Created 2025-01-16 00:00:29 UTC
Updated 2025-10-03 06:04:15 UTC by Admin